

630

SXCF 220 #1

Synthetic, Corrosion Resistant Machinery Grease

APPLICATION AREAS

- *Uniquely Suited for Medium to Large Bore Bearings*
 - *Designed for Wet, Hot, Corrosive Services*
- *Feeders, Mixers, Agitators*
 - *Conveyor Rollers*
- *Grease Lubricated Chains and Sprockets*
 - *Gears and Cams*
 - *Guides/Slides*
 - *Motor Drive Valves*
 - *Conveyor Drives*
- *Rotary Filling, Can Seemers, Bottle Washers*



PRODUCT DATA SHEET

KEY FEATURES AND BENEFITS

- Heat-stable 100% synthetic base stock
- Pumpable, non-clogging NLGI #1
- Calcium sulfonate complex technology improves resistance to water wash out and spray off
- NSF H1 - Registration number 157331
- Contains no animal fats or oils
- For use in food and non-food industries

PACKAGING

400 g, 18 kg, 55 kg, 180 kg

DIRECTIONS

Apply with a grease gun or automatic dispensers. Before using, wipe grease fittings to remove contamination. Keep grease container closed when not in use. Reapply at regular intervals.

DESCRIPTION

Chesterton 630 SXCF 220 #1 is a high base oil viscosity, high-performance synthetic grease that has excellent corrosion protection with superior resistance to water wash-out and spray off. It has a dropping point of 316°C (600°F), and excellent shear stability. It performs at temperatures well beyond that of most conventional petroleum greases. 630 SXCF 220 #1 will continue to lubricate even in the presence of heat, steam, hot water wash downs.

Uses of Chesterton 630 SXCF 220 #1 can be found throughout any industrial plants. It is especially advantageous where there are high temperatures and water environments such as in a pulp and paper mill, high moisture and water exposure such as in water/wastewater, marine, oil and gas applications, and extreme pressure such as in mining operations. 630 SXCF 220 #1 is NSF H1 registered and complies with FDA 178.3570 for use in food, beverage, and pharmaceutical processing equipment.

TYPICAL PHYSICAL PROPERTIES

Appearance	Off white
Consistency, NLGI	1
Texture	Smooth, buttery
Thickener	Proprietary, non-melting, sulfonate complex
Specific Gravity @ 25°C (77°F)	1.05
Viscosity ASTM D445, DIN 51 561	
@ 40°C	220 cSt
@ 100°C	25 cSt
Dropping Point (ASTM D 2265, DIN 51 801/1)	316°C (600°F)
Penetration (ASTM D 217, DIN ISO 2137)	310-340
Four Ball Wear Test (ASTM D 2266, DIN 51 350/5) Scar Diameter 40kg, 1200 rpm, 75°C, 1hr	0,45 mm
Four Ball Wear Test (ASTM D 2596, DIN 51 350/4) Weld Load Load Wear Index	400 kgf (3922 lbs) 53
Operating Temperature (above 180°C, increased lubrication frequency is required)	-40°C (-40°F) – 240°C (464°F)
Water Spray Off (ASTM D 4049)	30%
Water Washout (ASTM D 1264) @ 79°C	1%
Shear Stability (ASTM D 217), Change	
10000 strokes	<3.0
100000 strokes (estimated)	<4.0
Oil Separation (ASTM D 1742), % loss	<0.5%
Corrosion Resistance (ASTM B 117), 5% NaCl	>1200 hrs @ 50 micron film thickness
Lubricating Additives — non-heavy metal, extreme pressure and antiwear, anti-fretting additives, surface reactive anti rust and corrosion additives, oxidation inhibitors	
Bomb Oxidation (ASTM D 942) psi pressure drop, 100 hrs	<1
1000 hrs (estimated)	6
Copper Corrosion (ASTM D 4048, DIN 51 811)	1B
ISO/DIN Classification	ISO L X CF I B1 / DIN 51 502 K-LP 1 HC R1-40

Before using this product, please refer to Safety Data Sheet (SDS).



630

SXCF 220 #1

CHESTERTON GREASE SELECTION GUIDE

Technical Specifications and Features

AWC Grease	NLGI	ISO VG	nDm	Temperature	Water	Corrosion	Load/Vibration	Oil Bleed
613 Moly Grease	2	150	100 – 400	✓+	✓+	✓	✓+	✓+
615 HTG #1	1	100	70 – 300	✓+	✓++	✓++	✓++	✓++
615 HTG #2	2	100	70 – 300	✓+	✓++	✓++	✓++	✓++
615 HTG #2 460	2	460	<70	✓+	✓++	✓++	✓++	✓++
622 White Grease	2	100	50 – 300	✓+	✓+	✓+	✓	✓+
625 CXF	2	100	70 – 300	✓+	✓++	✓++	✓++	✓++
629 HTWG	2	220	50 – 300	✓+	✓++	✓+	✓	✓++
630 SXCF*	2	46	150 – 800	✓++	✓++	✓++	✓++	✓++
630 SXCF 220 #1	1	220	50 – 300	✓++	✓++	✓++	✓+	✓+
633 SXCM*	1	32	200 – 800	✓++	✓+	✓+	✓++	✓+
635 SXC	2	100	100 – 500	✓++	✓++	✓++	✓++	✓++

nDm x1000

* 630 and 633 for high speed and or temperatures < 0°C, 32°F

NLGI #1 preferred for multi point, central lube lines

✓++ – Best ✓+ – Better ✓ – Good

Application Recommendation

AWC Grease	Electric Motors	Conveyors	Pumps	Mixers/Agitators	Machinery
613 Moly Grease	✓	✓++	✓++	✓++	✓+
615 HTG #1	✓+	✓+	✓+	✓+	✓++
615 HTG #2	✓+	✓+	✓++	✓+	✓++
615 HTG #2 460	✓	✓++	✓++	✓++	✓++
622 White Grease	✓	✓+	✓+	✓+	✓+
625 CXF	✓++	✓+	✓++	✓++	✓++
629 HTWG	✓	✓	✓	✓	✓+
630 SXCF*	✓++	✓+	✓+	✓+	✓++
630 SXCF 220 #1	✓+	✓++	✓++	✓++	✓++
633 SXCM*	✓+	✓	✓+	✓	✓++
635 SXC	✓++	✓+	✓++	✓+	✓++

✓++ – Best ✓+ – Better ✓ – Good

nDm x1000

* 630 and 633 for high speed and or temperatures < 0°C, 32°F

NLGI #1 preferred for multi point, central lube lines